



Asia Petrochemicals LLC

Slack wax

PRODUCT DESCRIPTION

Slack wax is a mixture of oil and wax, obtained from lubricating oil. Slack wax is the crude wax produced by chilling and solvent filter-pressing wax distillate. It serves as feedstock and that is further refined and blended to create value-added petroleum wax products.

APPLICATIONS:

Slack Wax is widely used in the production of construction board, candles, wax emulsions, matches, rust protective products and moisture vapor barriers.

Packing: Iron Drum is the perfect packing for Slack Wax. The oily nature of Slack Wax prevents the possibility of packing in cartons or bags. Nonetheless, in cold seasons, when there is zero possibility of leakage, it can be packed in cartons or bags.

Characteristics	Specifications		
	Light Slack Wax	Heavy Slack Wax	Test Method ASTM
Drop melting point, °C	57	64	D-127
Oil content ,wt%	14	16	D-721
Color	0.5	0.5	D-1500
Specific gravity 25°C	0.890	0.890	IP-190
Flash point, °C	238	249	D-92
Kinematic viscosity@ 100°C, cSt	5.5	7.5	D-445

For further information please visit <http://www.asia-petrochem.com> or send an enquiry to info@asia-petrochem.com

Asia Petrochemicals LLC
PO Box 76283 Dubai UAE
T +971 4 2384533 F +971 4 2384534