



Asia Petrochemicals LLC

## Aromatic Rubber Processing Oil

### PRODUCT DESCRIPTION

The primary characteristics of aromatic hydrocarbons is the presence of the double mix ring carbon structure. Aromatic extracts procured from selected refineries and suitably blended to meet stringent specifications, are used for compounding batches to manufacture Tyres, Tubes, Hoses, Calender sheets etc.

**Packing:** 200Kgs/Drums, Bulk & Flexi

Specifications	Test Method	Unit	Result
<b>Kin. Viscosity @ 100°C</b>	ASTM D-445	Cst/SSU	20-30 Cst/ 100-160
<b>Specific Gravity @ 25°C</b>	ASTM D-1298		0.97-1
<b>Flash Point</b>	ASTM D-92	°C	230 (Min)
<b>Color</b>	ASTM D-1500	-	8 (Max)
<b>Pour Point</b>	ASTM D-	°C	24 (Max)
<b>Aniline Point</b>	IP-2	°C	45
<b>Sulfur Content</b>	ASTM D-2622	%M	3.6
<b>Ash Content</b>	ASTM D 482	%M	0.02

For further information please visit <http://www.asia-petrochem.com> or send an enquiry to [info@asia-petrochem.com](mailto:info@asia-petrochem.com)

Asia Petrochemicals LLC  
PO Box 76283 Dubai UAE  
T +971 4 2384533 F +971 4 2384534