



Asia Petrochemicals LLC

Group I - BS-150

PRODUCT DESCRIPTION

Bright Stock or BS is defined as a base oil at the upper end of the specifications for Grade I base oils. They are mainly used in lubricant and lubricant additive production. It is a Group I base oil which has undergone solvent refining and dewaxing processes. To finish the refining it was hydrogen treated to clear out any impurities.

APPLICATIONS:

- Engine oils
- Additives
- General purpose oils
- Gear oils
- Transmission fluids
- Gear oils
- Metal working fluids
- Hydraulic oils
- Transformer oils

Packing: Drum, Flexi & Bulk

PROPERTY	TEST METHOD	UNIT	RESULT
Appearance	ASTM D4176	0	B&C
Color	ASTM D1500	-	L 3.5
Density 15°C	ASTM D4052	Kg/ltr	0.9
Kinematic Viscosity 40°C	ASTM D445	cSt	460
Kinematic Viscosity 100°C	ASTM D445	cSt	30
Viscosity Index	ASTM D2270	-	95Min
Flash Point COC	ASTM D92	°C	308
Pour Point	ASTM D97	°C	-6
Carbon Residue	ASTM D189	Wt%	0.10
Acid Number (TAN)	ASTM D664	mgKOH/g	0.01
Total Sulphur Content	ASTM D2622	Wt%	0.652

For further information please visit <http://www.asia-petrochem.com> or send an enquiry to info@asia-petrochem.com

Asia Petrochemicals LLC
PO Box 76283 Dubai UAE
T +971 4 2384533 F +971 4 2384534