



Asia Petrochemicals LLC

Group II SN-500N

PRODUCT DESCRIPTION

SN 500N is a heavy GII base oil which is derived from refining of vacuum distillates of specific crude oil fractions by dewaxing and hydro-processing. They are mainly used in lubricant production where their typical parameters are used for specific products.

APPLICATIONS:

- 2T and 4T engine oils
- General purpose oils
- Mould oil
- Transmission fluids
- Gear oils
- Metal working fluids
- Hydraulic oils
- Transformer oils

Packing: Drum, Flexi & Bulk

PROPERTY	TEST METHOD	UNIT	RESULT
Appearance	Visual	-	Clear & Bright
Colour	ASTM D1500	-	0.5 MAX
*Flash Point	ASTM D92	°C	240 MIN
*Pour Point	ASTM D97	°C	-15 MAX
*Density @ 15°C	ASTM D1298	Kg/l	0.89 MAX
*Viscosity Kinematic @ 40°C	ASTM D445	cSt	95.00 MIN
*Viscosity Kinematic @100°C	ASTM D445	°C	11.00 MIN
Viscosity Index	ASTM D2270	-	100 MIN
*Sulphur Content	ASTM D4294-10	% m	0.776

For further information please visit <http://www.asia-petrochem.com> or send an enquiry to info@asia-petrochem.com

Asia Petrochemicals LLC
PO Box 76283 Dubai UAE
T +971 4 2384533 F +971 4 2384534