



Asia Petrochemicals LLC

Group II SN-600N

PRODUCT DESCRIPTION

SN 600N is defined as a light grade base oil at the lower end of the specifications for Grade I light base oils. They are mainly used in lubricant and lubricant additives production. It is a Group I base oil which has undergone solvent refining and dewaxing processes. To finish the refining it was hydrogen treated to clear out any impurities.

APPLICATIONS:

- 2T and 4T engine oils
- General purpose oils
- Mould oil
- Transmission fluids
- Gear oils
- Metal working fluids
- Hydraulic oils
- Transformer oils

Packing: Drum, Flexi & Bulk

PROPERTY	TEST METHOD	UNIT	RESULT	
Colour	ASTM D1500	-	Max 0.5	L0.5
Viscosity @40°C	ASTM D445	mm ² /S	Report	102.00
Viscosity @100°C	ASTM D445	mm ² /S	12.0~12.9	12.07
Viscosity Index	ASTM D2270		Min 95	107
Pour point	ASTM D6749 ASTM D5950	°C	Max -12	-14.0
Flash point	ASTM D92	°C	Min 246	275
Aromatics	ASTM D3238	%	Max 1.0	0.0
CCR	ASTM D189	wt%	Max 0.01	L0.01
TAN	ASTM D974	mgKOH/g	Max 0.01	0.005
Noack Volatility	ASTM D5800	wt%	X	X

For further information please visit <http://www.asia-petrochem.com> or send an enquiry to info@asia-petrochem.com

Asia Petrochemicals LLC
PO Box 76283 Dubai UAE
T +971 4 2384533 F +971 4 2384534