



Asia Petrochemicals LLC

Isopropyl Alcohol (Technical Grade) 45%

PRODUCT DESCRIPTION

Isopropanol is a colorless, flammable liquid with a characteristic alcoholic odor. It is completely miscible with most solvents, including water, and is a suitable solvent for acrylic and epoxy resins, ethyl cellulose, natural resins, gums, polyvinyl butyral, alkaloids and some essential oils.

APPLICATIONS:

- Nitrocellulose lacquers and thinners
- Coupling agent in cleaners and polishes
- Dehydrating agent
- Extractant
- Adhesives
- Pharmaceutical
- Cosmetics and toiletries
- Disinfectants
- Rubbing compounds
- Lithographic printing
- Chemical intermediate
- De-icing
- General purpose cleaners.

Packing: Bulk, ISO Tanks & Drums

PROPERTIES	UNITS	LIMITS	TEST METHODS	
			ASTM	OTHER
Appearance		Clear and free from suspended matter	D4176	Visual
Colour	Pt-Co	10 Max	D1209	
Water	Mass %	2.5 Max	D1364	
ISO-Propanol	Mass %	40 Min		GC
Density at 20°C	g/ml	0.800 Max	D4052	
Methanol	Volume %	60 Max		GC
Final boiling point	°C	83.0		

For further information please visit <http://www.asia-petrochem.com> or send an enquiry to info@asia-petrochem.com

Asia Petrochemicals LLC
PO Box 76283 Dubai UAE
T +971 4 2384533 F +971 4 2384534