



Asia Petrochemicals LLC

## Solvent Naphtha 150

### PRODUCT DESCRIPTION

Solvent Naphtha 150 is a colourless non-viscous liquid with a strong aromatic odour. It is not soluble in water, but in aromatic solvents.

### Applications

Solvent Naphtha 150 is used as a solvent in the paint and varnish industry. It is used mainly in metallic paints, but can also be found in varnishes and wood paints.

**Packing:** Bulk, ISO Tanks & Drums

PROPERTY	UNITS	TYPICAL VALUES	TEST METHOD
Distillation range	°C		ASTM D 86
IBP		183	
DP		207	
Flash Point	°C	66	ASTM D 56
Density @ 15°C	Kg/dm <sup>3</sup>	0.896	ASTM D 4052
Viscosity @ 25°C	mm <sup>2</sup> /s	1.21	ASTM D 445
Evaporation rate (n-BuAc=100)	-	10	EMC-AP-F01
KB value	-	95	ASTM D 1133
Aniline point	°C	15	ASTM D 611 mixed
Aromatic content	Vol %	99	ASTM D 1319
Colour (Saybolt)	-	+30	ASTM D 156
Bromine index	Mg/100g	250	ASTM D 2710
Surface tension @ 25°C	mN/m	30.5	Ec-M-F02
Refractive index @ 20°C	-	1.521	ASTM D 1218

For further information please visit <http://www.asia-petrochem.com> or send an enquiry to [info@asia-petrochem.com](mailto:info@asia-petrochem.com)

Asia Petrochemicals LLC  
PO Box 76283 Dubai UAE  
T +971 4 2384533 F +971 4 2384534